

STANDARD INVERTER (R32)

Optimized Air Flow for Cooling & Heating

- During cooling operation, the vane adjusts upwards to direct the air flow toward the ceiling. During heating operation, the van directs the air flow toward the floor to balance out the room temperature.
- Optional Two thermistors control, The indoor temperature can be checked using the thermistors in the remote controller as well as from the indoor unit.
- 5 step vane control for the air flow direction
- Smart Sensor (Temperature Sensor + Pressure Sensor) operation can reach desired Indoor temperature more rapidly.
- Mobile LGMV (monitoring View) helps engineers to inspect and monitor an air conditioning unit easily by mobile phone
- Easy Installation, 6 different ways to Install piping
- Easy Service, Easy Slide-Type PCB
- **Standard for Wi-Fi (Embedded)**
- **Standard for Ionizer**
- **Standard for Wireless controller with the indoor console unit.**

UQ09F / UQ12F / UQ18F



UUA1.U10

UUB1.U20



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com

COMBINATION				9	12	18
Capacity	Cooling	Min. / Rated / Max.	kW	1.5 / 2.6 / 3.4	1.5 / 3.5 / 4.0	2.0 / 5.0 / 5.8
	Heating	Min. / Rated / Max.	kW	1.6 / 3.1 / 3.9	1.6 / 4.0 / 4.3	2.0 / 4.9 / 5.4
Power Input (Set)	Cooling	Min. / Rated / Max.	kW	0.30 / 0.65 / 0.91	0.30 / 1.00 / 1.46	0.40 / 1.75 / 2.45
	Heating	Min. / Rated / Max.	kW	0.30 / 0.74 / 1.08	0.30 / 1.05 / 1.58	0.30 / 1.56 / 2.11
Running Current	Cooling / Heating	Rated	A	2.9 / 3.3	4.4 / 4.7	8.3 / 8.0
EER / COP			kWh / kWh	4.00 / 4.20	3.50 / 3.80	2.85 / 3.14
SEER / SCOP			kWh / kWh	6.5 / 4.0	6.4 / 4.0	5.8 / 3.8
Pdesign	Cooling @ 35°C		kW	2.6	3.5	5
	Heating @ -10°C		kW	2.8	3	3.8
Seasonal Energy Label	Cooling / Heating		-	A++ / A+	A++ / A+	A+ / A
Annual Energy Consumption	Cooling / Heating		kWh	140 / 980	191 / 1,050	302 / 1,396
Dehumidification Rate			l/h	0.7	1.3	2.4
ODU Sound Pressure Level*	Cooling / Heating	Rated	dB(A)	49 / 52	49 / 52	47 / 52
ODU Sound Power Level	Cooling	Rated	dB(A)	65	65	63
Piping Connections	Liquid / Gas		mm (inch)	Ø6.35 (1/4) / Ø9.52 (3/8)	Ø6.35 (1/4) / Ø9.52 (3/8)	Ø6.35 (1/4) / Ø12.7 (1/2)
	Connections Method		-	Flared	Flared	Flared
Operation Range (Outdoor)	Cooling	Min. / Max.	°C	-15 / 50	-15 / 50	-15 / 50
	Heating	Min. / Max.	°C	-20 / 18	-20 / 18	-20 / 18
INDOOR				UQ09F.NA0	UQ12F.NA0	UQ18F.NA0
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Input (IDU)		H / M / L	W	37 / 30 / 25	37 / 30 / 25	44 / 39 / 35
Air Flow Rate		H / M / L	m³/min	8.5 / 6.7 / 5.0	8.5 / 6.7 / 5.0	10.1 / 8.6 / 7.2
Dimensions	Body	W x H x D	mm	700 x 600 x 210	700 x 600 x 210	700 x 600 x 210
Weight	Body		kg	16.3	16.3	16.3
Sound Pressure Level*	Cooling	H / M / L	dB(A)	38 / 32 / 27	38 / 32 / 27	44 / 39 / 35
Sound Power Level	Cooling	Max.	dB(A)	59	59	60
Piping Connections	Drain	O.D. / I.D.	mm	Ø16.7 / 12.2	Ø16.7 / 12.2	Ø16.7 / 12.2
OUTDOOR				UUA1.U10	UUB1.U20	
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	
Circuit Breaker	Min.		A	15	20	
Power Supply Cable (Included Earth)			No x mm²	3C x 1.5	3C x 2.5	
Dimensions	Net	W x H x D	mm	770 x 545 x 288	870 x 650 x 330	
Weight	Net		kg	33.3	44.5	
Compressor	Type		-	Twin Rotary	Twin Rotary	
Refrigerant	Type / GWP (Global Warming Potential)		-	R32 / 675	R32 / 675	
	Precharged Amount / t-CO ₂ eq		kg	1.0 / 0.675	1.2 / 0.81	
	Chargeless		m	10	10	
	Additional Charging Volume		g/m	20	20	
Fan	Air Flow Rate	Rated	m³/min x No.	28 x 1	50 x 1	
Total Piping Length		Min. / Max.	m	5 / 30	5 / 30	
Piping Elevation	IDU - ODU	Max.	m	30	30	

* : Sound Pressure is not a value declared on Eurovent Program.

Note :

1. Due to our policy of innovation some specifications may be changed without notification.

2. Performances are based on the following conditions (It is accordance with EN14511)

- Cooling : Indoor Ambient Temp 27°C DB / 19°C WB, Outdoor Ambient Temp 35°C DB / 24°C WB

- Heating : Indoor Ambient Temp 20°C DB / 15°C WB, Outdoor Ambient Temp 7°C DB / 6°C WB

- Interconnected Pipe is standard length and difference of Elevation (Outdoor ~ Indoor Unit) is 0m.

3. Sound Level Values are measured at Noise Measuring chamber accordance with standard. Therefore, these values depend on the ambient conditions and values are normally higher in actual operation.

4. This product contains fluorinated greenhouse gases. (R32)

5. For our policy of continuous product improvement, specification, design and feature are subject to change without prior notice.